This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims (deleted text being struck through and added text being underlined):

1. (Previously Presented) A vehicle disabling system comprising:

a vehicle control unit for positioning in a vehicle, the vehicle control unit including a transceiver for transmitting and receiving signals via free space, the transceiver including means for receiving an inquiry signal and transmitting an identification code upon the receipt of the inquiry signal;

a central database station including memory for storing a plurality of identification codes of vehicle control units, an authorization code being associated in the memory with each of the identification codes of the vehicle control units; and

a mobile law enforcement unit for positioning in a law enforcement vehicle, the law enforcement unit including a transceiver for transmitting and receiving signals via free space, the law enforcement unit including means for transmitting the inquiry signal to the vehicle control unit, the law enforcement unit including means for receiving an identification code from the vehicle control unit and transmitting the identification code to central database station, the law enforcement unit including means for transmitting the stop signal with the authorization code via free space to the vehicle control unit upon the receipt of the

wherein the vehicle control unit includes means for connecting to an ignition system of the vehicle, the vehicle control unit including means for lowering an engine speed of the vehicle to an

authorization code from the central database station;

1

2

3

4

5

6

7

8

12

13

14

15

16

17

18

19

20

21

22

23

24

- 26 idle condition upon the receipt by the transceiver of a stop signal
- 27 accompanied by an authorization code via free space within a
- 28 predetermined amount of time after receipt of the inquiry signal.
- 2. (Previously Presented) The system of claim 1 wherein the vehicle control unit includes means for connecting to at least one exterior light circuit of the vehicle such that exterior lights of the vehicle are flashable by the vehicle control unit upon receipt of the inquiry signal by the transceiver to provide external visual confirmation of receipt of the inquiry signal by the vehicle control unit.



1

3. (Cancelled)

- 4. (Previously Presented) The system of claim 1 wherein the vehicle control unit includes means for connecting to a horn of the vehicle such that the vehicle control unit actuates the horn of the vehicle upon the receipt by the transceiver of a stop signal accompanied by an authorization code via free space within a predetermined amount of time after receipt of the inquiry signal.
- 5. (Currently Amended) The system of claim 3 1 wherein the predetermined amount of time is approximately 30 seconds.
- 6. (Original) The system of claim 4 wherein the predetermined amount of time is approximately 30 seconds.

7. (Previously Presented) A vehicle disabling system comprising:

a vehicle control unit for positioning in a vehicle, the vehicle control unit including a transceiver for transmitting and receiving signals via free space, the transceiver including means for receiving an inquiry signal and transmitting an identification code upon the receipt of the inquiry signal, the vehicle control unit being connectable to at least one exterior light circuit of the vehicle such that exterior lights of the vehicle are flashable by the vehicle control unit upon receipt of the inquiry signal by the transceiver to provide external visual confirmation of receipt of the inquiry signal by the vehicle control unit, the vehicle control unit being connectable to an ignition system of the vehicle, the vehicle control unit including means for lowering an engine speed of the vehicle to an idle condition upon the receipt by the transceiver of a stop signal accompanied by an authorization code via free space within a predetermined amount of time after receipt of the inquiry signal, the vehicle control unit includes means for connecting to a horn of the vehicle such that the vehicle control unit actuates the horn of the vehicle upon the receipt by the transceiver of a stop signal accompanied by an authorization code via free space within a predetermined amount of time after receipt of the inquiry signal, wherein the predetermined amount of time is approximately 30 seconds; a central database station including memory for storing a plurality of identification codes of vehicle control units, an

a central database station including memory for storing a plurality of identification codes of vehicle control units, an authorization code being associated in the memory with each of the identification codes of the vehicle control units; and

a mobile law enforcement unit for positioning in a law enforcement vehicle, the law enforcement unit including a



1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

18

19

20

21

22

23

24

25

26

27

28

29

transceiver for transmitting and receiving signals via free space, the 31 law enforcement unit includes means for transmitting the inquiry 32 signal to the vehicle control unit, the law enforcement unit includes 33 means for receiving an identification code from the vehicle control 34 35 unit and transmitting the identification code to central database station, the law enforcement unit includes means for transmitting 36 the stop signal with the authorization code via free space to the 37 vehicle control unit upon the receipt of the authorization code from 38 39 the central database station.

8. (Previously Presented) A method of disabling a vehicle comprising the steps of:

providing a vehicle control unit for positioning in the vehicle, the vehicle control unit including a transceiver for transmitting and receiving signals via free space;

providing a central database station including memory for storing a plurality of identification codes of vehicle control units, the memory of the central database storing an authorization code associated with each of the identification codes of the vehicle control units;

providing a mobile law enforcement unit for positioning in a law enforcement vehicle, the law enforcement unit including a transceiver for transmitting and receiving signals via free space;

transmitting an inquiry signal from the law enforcement unit to the vehicle control unit;

transmitting an identification code from the vehicle control unit to the law enforcement unit;

transmitting the identification code from the law enforcement unit to the central database station;

matching an authorization code from the memory of the central database station to the identification code; and



1

2

3

4

5

6

7

8

9

10

11

12

13

14

15

16

17

20

transmitting a stop signal from the law enforcement unit to the vehicle control unit; and

lowering an engine speed of an engine of the vehicle by the vehicle control unit upon the receipt by the vehicle control unit of the stop signal so that the engine of the vehicle is put into an idle condition.

- 9. (Original) The method of claim 8 additionally comprising transmitting the authorization code to the law enforcement unit.
- 1 10. (Previously Presented) The method of claim 9 additionally comprising transmitting the authorization code from the law enforcement unit to the vehicle control unit.

11. (Cancelled)

- 12. (Original) The method of claim 10 additionally comprising actuating a horn of the vehicle upon the receipt by the vehicle control unit of the stop signal accompanied by the authorization code.
- 13. (Original) The method of claim 8 additionally comprising flashing exterior lights of the vehicle by the vehicle control unit upon receipt of the inquiry signal by the vehicle control unit to provide external visual confirmation of receipt of the inquiry signal by the vehicle control unit.
- 14. (Previously Presented) The system of claim 1 wherein the vehicle control unit includes means for transmitting a signal to a powertrain control module of the vehicle, and the powertrain control module includes means for causing an engine of the vehicle to return to idle and causing a check engine light of the vehicle to



1

2

1

2

3

4

1

2

3

4

5

2

3

4

5



- illuminate when the powertrain control module does not receive the
- 8 signal from the vehicle control unit.